

United States Patent and Trademark Office

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.	
10/044,636	10/19/2001	Sidney T. Smith	FLM-5169	8615	
7	590 12/08/2005		EXAMINER		
MARK J. BUONAIUTO, ESQ. BAXTER INTERNATIONAL INC.			BISSETT, MELANIE D		
LAW DEPAR		ART UNIT	PAPER NUMBER		
ONE BAXTER PARKWAY, DF2-2E					
DEERFIELD,	IL 60015		DATE MAILED: 12/08/2005		

Please find below and/or attached an Office communication concerning this application or proceeding.

		Application No.	Applicant(s)	- V
		10/044,636	SMITH ET AL.	
Office Action 3	Summary	Examiner	Art Unit	
		Melanie D. Bissett	1711	
The MAILING DATE Period for Reply	of this communication ap	pears on the cover sheet with	the correspondence address	
A SHORTENED STATUTO WHICHEVER IS LONGER - Extensions of time may be available after SIX (6) MONTHS from the mai - If NO period for reply is specified ab - Failure to reply within the set or exte	FROM THE MAILING D under the provisions of 37 CFR 1. ing date of this communication. ove, the maximum statutory period nded period for reply will, by statut r than three months after the mailing	DATE OF THIS COMMUNICA 136(a). In no event, however, may a rep	ly be timely filed IS from the mailing date of this communi NDONED (35 U.S.C. § 133).	
Status				
2a) ☐ This action is FINAL . 3) ☐ Since this application	is in condition for allowa	s action is non-final.	rs, prosecution as to the meri	its is
	with the practice under	Ex parte Quayle, 1905 C.D.	11, 455 O.G. 215.	
Disposition of Claims				
4a) Of the above clair 5) ☐ Claim(s) is/are 6) ☑ Claim(s) 3-7,9-18,20, 7) ☐ Claim(s) is/are 8) ☐ Claim(s) are s Application Papers 9) ☐ The specification is of	n(s) is/are withdra allowed. 22,23,25,26,28,39-45,6 objected to. ubject to restriction and/objected to by the Examin	<u>1 and 62</u> is/are rejected. or election requirement.		
Applicant may not requ	est that any objection to the	e drawing(s) be held in abeyance	e. See 37 CFR 1.85(a).	
<u> </u>	• •) is objected to. See 37 CFR 1.1 Office Action or form PTO-15	• •
Priority under 35 U.S.C. § 119				
12) Acknowledgment is m a) All b) Some * of 1. Certified copies 2. Certified copies 3. Copies of the of application from	ade of a claim for foreign c) None of: s of the priority document of the priority document ertified copies of the prior of the International Burea	its have been received in Apports documents have been re	plication No eceived in this National Stage	e
Attachment(s) 1) Notice of References Cited (PTC 2) Notice of Draftsperson's Patent 3) Information Disclosure Statemer Paper No(s)/Mail Date	Drawing Review (PTO-948)	Paper No(s)/	mmary (PTO-413) Mail Date ormal Patent Application (PTO-152)	

Art Unit: 1711

1. This action replaces the action mailed 29 November 2005. The previous action was mistakenly mailed as a final action. The present action is non-final.

2. The rejections have been altered to reflect the amended claims.

Claim Rejections - 35 USC § 112

- 3. The following is a quotation of the first paragraph of 35 U.S.C. 112:
 - The specification shall contain a written description of the invention, and of the manner and process of making and using it, in such full, clear, concise, and exact terms as to enable any person skilled in the art to which it pertains, or with which it is most nearly connected, to make and use the same and shall set forth the best mode contemplated by the inventor of carrying out his invention.
- 4. Claims 3-7, 9-18, 20, 22-23, 25-26, 28, 39-45, and 61-62 are rejected under 35 U.S.C. 112, first paragraph, as failing to comply with the written description requirement. The claim(s) contains subject matter which was not described in the specification in such a way as to reasonably convey to one skilled in the relevant art that the inventor(s), at the time the application was filed, had possession of the claimed invention.
- 5. Independent claims 18 and 39 have been amended to contain the recitation of a "DSC melting point of about 100 °C". The applicant relies upon an example of Affinity PL 1880 for the support of this limitation. The Affinity material has a DSC melting point of 99-100 °C. It is the examiner's position that the recitation of this material in the specification does not support the entire range of "about 100 °C", since the word "about" would encompass a broader range than the experimental error range of the melting point determination. It is the examiner's position that the example does not support all materials having a melting point of 100 °C, either, since all materials are encompassed

Art Unit: 1711

by the claim and one specific example is given. Thus, the example only provides support for the use of the specific layer structure shown and nothing broader.

Claim Rejections - 35 USC § 102

- 6. The text of those sections of Title 35, U.S. Code not included in this action can be found in a prior Office action.
- 7. Claims 4-7, 9-18, 20, 22-23, 25-26, 28, 39-45, and 61 are rejected under 35 U.S.C. 102(e) as being anticipated by Smith et al. as evidenced by DuPont.
- 8. From a prior Office action:

The applied reference has a common inventor with the instant application. Based upon the earlier effective U.S. filing date of the reference, it constitutes prior art under 35 U.S.C. 102(e). This rejection under 35 U.S.C. 102(e) might be overcome either by a showing under 37 CFR 1.132 that any invention disclosed but not claimed in the reference was derived from the inventor of this application and is thus not the invention "by another," or by an appropriate showing under 37 CFR 1.131.

Smith teaches a multiple layer structure having solution contact and outer exterior layers, where the outer layers are chosen from polyamides, polyesters, and polyolefins (abstract). The modulus of the overall film is less than 50,000 psi (col. 3 lines 18-28). Polyamide materials include ring-opening products nylon 6, nylon 10, or nylon 12, while condensation products nylon 66, nylon 6,10, and dimmer fatty acid polyamides are also included (col. 4 lines 1-14). Single-site catalyzed polyolefins are used, where ethylene-butene copolymers are preferred (col. 4 lines 57-67). Affinity and Exact materials are used, and the copolymers should have densities of 0.880-0.910 g/cc (col. 5 lines 1-3). Tie layers include blends of modified and unmodified polyolefins, where maleic anhydride is a preferred modifying agent (col. 5 lines 4-47). The thicknesses of the layers read on the applicant's claimed ranges (col. 5 line 66-col. 6 line 10).

Regarding slip agents, the reference does not require the use of such slip agents; thus, it is the examiner's position that the reference teaches structures essentially free of slip agents. The layers are coextruded and formed into medical containers (col. 6 lines 38-60).

Regarding the burst pressure of the films, it is noted that the prior art films are made of the same materials and thicknesses as employed by the applicant. Thus, it is the examiner's position that the structures would inherently possess the applicant's claimed burst pressure values.

Regarding the "attached directly" language, the claims are interpreted in the broadest sense; the outer layer of Smith is attached directly to the inner layer through tie and barrier layers.

Application/Control Number: 10/044,636

Art Unit: 1711

9. Regarding the limitation of a DSC melting point, Smith discusses many tie layer materials, including Bynel, Plexar, and other modified and unmodified polyolefins (col. 5 lines 4-54). The reference exemplifies the use of Bynel 4206, which DuPont discloses as having a DSC melting point of 102 °C. It is the examiner's position that this melting point is within experimental error of 100 °C and also within the claimed range of "about 100 °C".

Page 4

- 10. Regarding the "sole tie layer" limitation, it is the examiner's position that any intermediate layers could be considered together as a sole tie layer, since they serve to bridge the first and second exterior layers to each other.
- 11. Claims 4-7, 9-10, 14-18, 20, 22-23, 25-26, 28, 39-41, and 61 are rejected under 35 U.S.C. 102(e) as being anticipated by Ramesh et al. '392 as evidenced by MatWeb.

12. From a prior Office action:

Ramesh discloses multi-layered films comprising a polyolefin outer layer and an outer layer selected from polyester, polyamide, and polyurethane (abstract). The polyolefin layer comprises a single-site catalyzed homogeneous ethylene/ α -olefin polymer having a preferred melting point below 100 °C and a preferred carbon content of 4-8 carbons in the α -olefin (col. 11-col. 12 line 3). The polyolefin also preferably has a density of less than 0.898 g/cc to create a layer of up to 4-mil thickness (col. 15 lines 28-58; col. 16 lines 22-23). Materials for the other outer include the applicant's claimed nylon materials at a thickness of up to 4 mils (col. 19 lines 22-28, 49-50). Tie layers are included at a thickness of 0.13 or 0.16 mils (col. 20 lines 16-20; example 1). The overall films have modulus values as low as 40,000 psi (col. 20 lines 42-50).

Regarding slip agents, the reference does not require the use of such slip agents; thus, it is the examiner's position that the reference teaches structures essentially free of slip agents. The layers are coextruded and formed into packaging containers (col. 1 lines 7-11; examples).

Regarding the burst pressure of the films, it is noted that the prior art films are made of the same materials and thicknesses as employed by the applicant. Thus, it is the examiner's position that the structures would inherently possess the applicant's claimed burst pressure values.

Art Unit: 1711

Regarding the "attached directly" language, the claims are interpreted in the broadest sense; the outer layers of Ramesh are attached directly to each other through tie and intermediate layers.

- 13. Regarding the limitation of a DSC melting point, Ramesh discloses many tie layer materials (col. 17 lines 9-26; examples). The term "below 100 °C" would overlap the claimed range of "about 100 °C".
- 14. Regarding the "sole tie layer" limitation, the reference appears to teach a single tie layer. Also, any intermediate layers could be considered together as a sole tie layer, since they serve to bridge the first and second exterior layers to each other.

Claim Rejections - 35 USC § 103

- 15. The text of those sections of Title 35, U.S. Code not included in this action can be found in a prior Office action.
- 16. Claims 11-13 and 42-45 are rejected under 35 U.S.C. 103(a) as being unpatentable over Ramesh et al. in view of Adur et al.

17. From a prior Office action:

Ramesh applies as above, teaching the use of tie layers but failing to specify a blend of a modified polyethylene copolymer with a polyolefin polymer. Adur teaches adhesive blends of grafted polyethylene homopolymers or copolymers, LDPE or LLDPE, and a poly(α -olefin), where the blends have improved adhesive strength with both polyolefins and polar substrates (col. 1 lines 36-56; col. 2 lines 4-10). The adhesives can be applied to substrates and co-extruded to form a number of articles (col. 1 lines 57-68). Examples of specific composites are listed, including polyolefin/adhesive/nylon, polyolefin/adhesive/EVOH, and polyolefin/adhesive/polyester (col. 4 lines 15-27). Maleic anhydride is noted as a preferred modifying monomer (col. 2 lines 49-65; examples 40-41, at least). Therefore, it is the examiner's position that it would have been prima facie obvious to use the adhesive blend of Adur's teaching in the composite of Ramesh's invention to improve the adhesive strength between the polyolefin and polar substrate.

Art Unit: 1711

18. Claims 3 and 62 are rejected under 35 U.S.C. 103(a) as being obvious over Smith et al. in view of Mueller.

19. From a prior Office action:

The applied reference has a common inventor with the instant application. Based upon the earlier effective U.S. filing date of the reference, it constitutes prior art only under 35 U.S.C. 102(e). This rejection under 35 U.S.C. 103(a) might be overcome by: (1) a showing under 37 CFR 1.132 that any invention disclosed but not claimed in the reference was derived from the inventor of this application and is thus not an invention "by another"; (2) a showing of a date of invention for the claimed subject matter of the application which corresponds to subject matter disclosed but not claimed in the reference, prior to the effective U.S. filing date of the reference under 37 CFR 1.131; or (3) an oath or declaration under 37 CFR 1.130 stating that the application and reference are currently owned by the same party and that the inventor named in the application is the prior inventor under 35 U.S.C. 104, together with a terminal disclaimer in accordance with 37 CFR 1.321(c). For applications filed on or after November 29, 1999, this rejection might also be overcome by showing that the subject matter of the reference and the claimed invention were, at the time the invention was made, owned by the same person or subject to an obligation of assignment to the same person. See MPEP § 706.02(I)(1) and § 706.02(I)(2).

Smith applies as above, teaching specific polyamides and also teaching copolyesters for use as outer layers but failing to note the use of the applicant's claimed polyester ethers. Mueller teaches multilayer films for flexible container purposes, where Ecdel materials are taught as equivalent to nylon 66, nylon 6,10, and nylon 12 as materials providing improved heat resistance and abuse resistance (col. 9 lines 37-53). Ecdel materials are noted by the applicant as PCCE polymers. It is the examiner's position that it would have been prima facie obvious to use PCCE polymers as outer layers in Smith's invention to provide multilayer films having equally improved heat resistance and abrasion resistance.

20. Claims 3 and 62 are rejected under 35 U.S.C. 103(a) as being unpatentable over Ramesh et al. '392 in view of Mueller.

21. From a prior Office action:

Ramesh applies as above, teaching specific polyamides and also teaching polyesters for use as outer layers but failing to note the use of the applicant's claimed polyester ethers. Mueller teaches multilayer films for flexible container purposes, where Ecdel materials are taught as equivalent to nylon 66, nylon 6,10, and nylon 12 as materials providing improved heat resistance and abuse resistance (col. 9 lines 37-53). Ecdel materials are noted by the applicant as PCCE

Art Unit: 1711

polymers. It is the examiner's position that it would have been prima facie obvious to use PCCE polymers as outer layers in Ramesh's invention to provide multilayer films having equally improved heat resistance and abrasion resistance.

Response to Arguments

22. The applicants argue that the references teach away from the claimed invention because they teach additional layers between the exterior layers. As previously stated, the claims are interpreted in their broadest sense to allow for intermediate layers. The exterior layers of the references are directly attached through intermediate layers. In the case of the DuPont reference, the exterior layers are attached directly through intermediate sublayers, where the tie/core/tie structure constitutes a sole layer. This same logic applies to the Ramesh reference. Again, it is the examiner's position that "attached directly" encompasses the presence of intermediate layers. The examiner suggests "attached directly and in intimate contact with" language to exclude intermediate layers between two defined layers. However, it is also the examiner's position that a tie layer can contain sublayers, and so a "sole tie layer" can include intermediate sublayers. By its broadest interpretation, a "tie layer" includes any intermediate layer connecting the two exterior layers.

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Melanie D. Bissett whose telephone number is (571) 272-1068. The examiner can normally be reached on M-F 8-4:30.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, James Seidleck can be reached on (571) 272-1078. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

Melanie D. Bissett Primary Examiner Art Unit 1711

mdb